

## REVAMP2150

Stereo Digital amplifier, convection cooled



The new all-purpose REVAMP2150 is a professional 2-channel digital power amplifier with 2 x 165 watts dynamic output power @ 4 ohms, that can easily be bridged into a powerful 330 watts @ 8 ohms single amplifier. This class-D amplifier is convection cooled without built-in fans which implies that the amplifier is completely noiseless and dust-free at all times. The unit has multiple speaker and amp protection circuits built inside for DC protect, over current protect, over temperature protect and protection against input overload.

During the configuration of the input gain, the rear clip LED indicator is very useful and handy for a fast and easy installation. Versatile connectivity due to balanced and unbalanced inputs on euroblock or cinch, pass-through outputs on cinch and loudspeaker outputs on euroblock. Housed in a straightforward 1U slim and lightweight design without front control our REVAMP2150 is an amplifier unlike any other in the small and mid-sized fixed install audio market.

### TECHNICAL SPECIFICATIONS

|  |               |  |                             |
|--|---------------|--|-----------------------------|
| dynamic output power 4 ohms in watts         | 2 x 165       | RMS output power 4 ohms in watts                   | 2 x 150                     |
| dynamic output power 8 ohms in watts         | 2 x 95        | RMS output power 8 ohms in watts                   | 2 x 80                      |
| dynamic output power bridged 8 ohms in watts | 330           | output power RMS bridged 8 ohms in watts           | 300                         |
| minimum impedance load per channel in ohms   | 4             | minimum impedance load bridged per channel in ohms | 8                           |
| power consumption (max) in watts             | 400           | 19" (483 mm wide) rack mounting                    | yes                         |
| height- rack units (1U=44 mm) in U           | 1             | height in mm                                       | 44                          |
| depth (build in) in mm                       | 230           | depth (incl front) in mm                           | 239                         |
| power supply                                 | 115 - 230 VAC | power supply technology                            | switching mode power supply |
| output channels                              | 2             | line input balanced                                | 2                           |
| line input unbalanced                        | 2             | channel separation                                 | > 70 dB @ 1 kHz             |
| power amp topology                           | class-D       | frequency response (in Hz)                         | 20 - 22 k                   |
| cooling system                               | convection    | applicable in 100V                                 | no                          |
| applicable low impedance                     | yes           | Net weight product (kg)                            | 3.2                         |

MORE PICTURES

