




# SUB 12A

## POWERED SUBWOOFER

Subwoofer series takes advantage of tremendous experience in touring, installation and mobile markets. Cabinets are equipped with next-generation transducers with reinforced moving system capable of withstanding tremendous pressure and excursion while keeping distortion in check.

Sub 12A is a compact powered subwoofer for mobile sound reinforcement and small installations. Equipped with 12" long excursion woofer, it is capable of impressive power output with small overall system size.



### Main features:

- 650 W amplifier power
- 12" woofer with 3" voice coil
- Efficient vented box design
- 127,5 dB Max SPL
- M20 distance pole adapter

Frequency Response (-10dB)	43 - 170 Hz
Max SPL (calculated)	127,5 dB
LF Driver	12", 3" VC
Amplifier power	650 W
Amplifier	Class D, fan cooling, DSP
Input sensitivity	0 dBV (1 V RMS)
Connectors	XLR input, XLR output, Powercon mains
Dimensions (W×H×D)	390x460x443 mm
Net weight	32 kg
Shipping weight	35 kg
Mounting	M20 distance pole adapter
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, acoustically transparent foam

With dedication to constant improvement of the products, manufacturer may change the listed specifications without prior notice